

# UFORCE SERIES

2018 UFORCE800



**CFMOTO**  
EXPERIENCE MORE TOGETHER

# UFORCE 800

T1b



T1b

## 10.2 IN. OF GROUND CLEARANCE

For maximum performance in challenging terrain, the Uforce 800 has total 260 mm (10.2 in) of ground clearance and 650 mm (25.6 in) of fording depth, which can tackle brutal conditions and cover all kinds of ground – wet or dry.

## SAFETY

## EPS

As an optional detail, EPS offers greater handling and steering feel while improving vehicle safety by adapting the steering torque to the vehicle's speed and providing active torque in critical driving situations.

## 1 SEATS AND TILT STEERING

Remote-control winch lets you easily get out of even the toughest situation. You can also control the look of your machine with awesome optional details like a windscreen, roof, side nets or bumpers and available in four stunning colors.



## 2 DUMP BOX

Tilt-assist dump box with payload capacity of 230 kg (507 lb), and 26-litre fuel tank capacity let you haul even more tough stuff farther. Rugged bed rails are included in the Uforce family package that adds more tie-down points for cargo carrying.



## 3 WINCH AND OTHER DETAILS

Adjustable tilt steering, besides providing maximum security and convenience, ergonomically designed seats even have an adjusting range of 144 mm (5.67 in) for extra comfort, the removable setup means you can always have comfortable seating, whether you're in the cab or sitting around the campfire.



# UFORCE 300



# UFORCE 350



Crystal Orange



Titanium Grey



Hunting Camo Maple

Copyright Zhejiang CFMOTO Power Co., Ltd. 2008. All rights reserved. Vehicle specifications are subject to change without notice. Imagery may not reflect most current product specifications. CFMOTO reserves the right to make improvements and/or design changes without any obligation to notify previously sold, assembled or fabricated equipment.

## ZHEJIANG CFMOTO POWER CO., LTD.

No. 116, Wuyihu Road, Yuhang Economic Development Zone,  
Hangzhou 311100, Zhejiang Province  
Tel: 86-571-89285799 Fax: 86-571-89285788  
Email: export@cfmoto.com, www.cfmoto.cn

## OVERALL DIMENSIONS 800/550

Length x Width x Height	2980 x 1430 x 1885 mm	2980 x 1465 x 1850 mm
wheelbase	1830 mm	1830 mm
seat height	445 mm	445 mm
Minimum Ground Clearance	260 mm	260 mm
Minimum Turning Diameter	9.5 m	9.5 m
Curb Weight	625 kg	634 kg
Payload Capacity	310 kg	310 kg
Fuel Capacity	26 L	26 L
Maximum Speed	100 km/h	84 km/h

## ENGINE

Engine Type	V-Twin cylinder, Liquid cooled, 4-stroke, SOHC, 8-Valve	Single-cylinder, Liquid cooled, 4-stroke, SOHC, 4-Valve
Displacement	600 cc	495 cc
Bore x Stroke	91 x 61.5 mm	91.0 x 76.2 mm
Maximum Power	46 kW / 6700 rpm	28 kW / 6800 rpm
Maximum Torque	72 N.m / 6000 rpm	43 N.m / 5800 rpm
Compression Ratio	10.3:1	10.3:1
Fuel Supply	EFI	EFI
Ignition	ECU	ECU
Transmission	CVT	CVT

## CHASSIS

Drive	Switchable 2WD / 4WD	Switchable 2WD / 4WD
Brake	Front/Rear: Hydraulic	Front/Rear: Hydraulic
Suspension	Front/Rear: Double arm, independent suspension	Front/Rear: Double arm, independent suspension
Shock Absorber	Front/Rear: coil spring oil shock absorber	Front/Rear: coil spring oil shock absorber
Rim	Front: 14 x 7.0 AT Aluminum Alloy / Radial Rear: 14 x 8.0 AT Aluminum Alloy / Radial	Front: 14 x 7.0 Aluminum Alloy / Radial Rear: 14 x 8.0 AT Aluminum Alloy / Radial
Tire Pressure	Front: 26 x 9.00-14; 26 x 9.00 R14 Rear: 26 x 11.00-14; 26 x 11.00 R14	Front: 26 x 9.00-14; 26 x 9.00 R14 Rear: 26 x 11.00-14; 26 x 11.00 R14